



## COCONUT SHELL GRANULAR ACTIVATED CARBON FOR WATER PURIFICATION

TYPE- COC-L60: COCONUT SHELL GRANULAR ACTIVATED CARBON IS DESIGNED FOR WATER PURIFICATION INCLUDING POTABLE WATER, BEVERAGE WATER, AQUARIUM WATER FILTRATION WASTEWATER TREATMENT AND TREATMENT WATER FOR HEMODIALYSIS.

COCONUT SHELL CARBON REMOVES CHLORINE, MONOCHLORAMINE, LEAD TCE, PCE, TTHMs, PHENOLS, PESTICIDES, DETERGENTS, TASTE AND ODOR FROM WATER.

<b>ACTIVATION METHOD:</b>	HIGH TEMPERATURE SOFT WATER STEAM
<b>CARBON TYPE:</b>	COC- L60 55 - 60 CTC (ASTM 3467)
<b>PARTICLE SIZE:</b>	12 X 40 US MESH
<b>BULK DENSITY:</b>	0.50 – 0.52 mg/cc (ASTM 2864)
<b>SPECIFIC SURFACE AREA:</b>	1100 - 1150 m <sup>2</sup> /gm
<b>ASH CONTENT:</b>	3.0% MAXIMUM
<b>MOISTURE AS PACKED:</b>	3.0% MAXIMUM (ASTM 2867)
<b>IODINE NUMBER:</b>	1100 - 1150

STANDARD PACKING: 55 POUND POLYLINE D POLYPROPYLENE BAGS, 220 POUND FIBER DRUMS AND 110 POUND SUPER SACKS ARE AVAILABLE.

TYPICAL 30 POUNDS PER CUBIC FOOT.

SHIPPING INFORMATION: F.O.B. OUR WAREHOUSE IN BUENA PARK, CALIFORNIA